

# emco Bau

## Clean-off system INNOVA

|   |   |
|---|---|
| Model   | INNOVA  |
| Construction                                    | Tufting velour 5/32"  |
| Pile above substrate                            | 100% polyamide  |
| Substrate material                              | Polyester fleece  |
| Backing material                                | Heavy coating   |
| Pile weight / fibre weight                      | 885 g/m <sup>2</sup>  |
| Total weight (g/m <sup>2</sup> )                | 3460 g/m <sup>2</sup>   |
| Overall height (mm)                             | 8 mm  |
| Slip resistance                                 | DS (EN 13893)   |
| Certificates                                    | CE conformity EN 14041 (rolls only)   |
| Colour fastness to artificial light ISO 105-B02 | good 5-6  |
| Colour fastness to rubbing ISO 105 X12          | good 4-5  |
| Colour fastness to water ISO 105 E01            | good 4-5  |
| Supplied as rolls                               | 200 cm wide (incl. border)<br>100 cm wide (incl. border)<br>150 cm wide (incl. border)  |
| Supplied as mats                                | 60 x 90 cm (incl. border)<br>90 x 150 cm (incl. border)<br>130 x 200 cm (incl. border)<br>200 x 300 cm (incl. border)   |
| Product characteristics                         | Soiling and moisture absorption   |
| Brand   | emco  |
| Contact   | emco Bautechnik GmbH · Breslauer Straße 34 - 38 ·<br>D-49808 Lingen (Ems) · Phone: +49 (0) 591/9140-500 · Fax:<br>+49 (0) 591/9140-852 · Email: bau@emco.de ·<br>www.emco-bau.com |
| Combustion/fire behaviour                       | Cfl-s1  |
| Colours   | 36.01 black<br>36.02 anthracite<br>36.03 grey<br>36.04 brown<br>36.05 red<br>36.10 slate  |