

# emco Bau

## Clean-off system MAXIMUS®

Model	MAXIMUS®
Construction	Tufting-Velours 1/8"
Pile above substrate	100% polyamide
Substrate material	Polyester fleece
Backing material	Heavy coating
Pile weight / fibre weight	1000 g/m <sup>2</sup>
Total weight (g/m <sup>2</sup> )	3410 g/m <sup>2</sup>
Overall height (mm)	9 mm
Slip resistance	DS (EN 13893)
Certificates	CE conformity EN 14041 (rolls only)
Colour fastness to artificial light ISO 105-B02	good 5-6
Colour fastness to rubbing ISO 105 X12	good 5
Colour fastness to water ISO 105 E01	good 5
Supplied as rolls	130 cm wide (incl. border) 200 cm wide (incl. border)
Supplied as mats	60 x 90 cm (incl. border) 90 x 150 cm (incl. border) 130 x 200 cm (incl. border)
Product characteristics	Soiling and moisture absorption
Brand	emco
Contact	emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems) · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de · www.emco-bau.com C/R/O/ GmbH · Handelsgesellschaft für Bodenbeläge · Memeler Straße 30 · D-42781 Haan · Telefon: 0 21 29/34 75 80 · Telefax: 0 21 29/34 75 810 · E-Mail: info@cro.de · www.cro.de
Combustion/fire behaviour	Bfl-s1

## Colours

Black 80.01  
Black mottled 81.01  
Anthracite 80.02  
Brown 80.04  
Red 80.07  
82.01 black Ambiente  
82.02 anthracite Ambiente  
82.03 grey Ambiente  
82.06 blue Ambiente  
82.07 red Ambiente  
Anthracite mottled 81.02  
Grey 80.03  
Grey mottled 81.03  
Brown mottled 81.04  
Beige 80.05  
Beige mottled 81.05  
Blue 80.06  
Bordeaux single colour 80.08