
# **Model 772**





### Description

Rigid floor grating. Safe, stable and sound workmanship. Its high specific weight prevents the floor grating from floating in water. Special shapes that are circular or with angles available.

#### Colours





# emco floor gratings

# **Model 772**

Material	High quality, extremely hard-wearing plastic, with UV absorber.  Entirely corrosion-free and resistant to chlorine, sea water and spa water.  No need for any metal parts; surface enclosed on all sides to provide maximum hygiene.
Support chassis	Full profile  (27 x 10 mm)  Underside of grating equipped with 10 mm-high rubber feet
Finish	Flat upper profile surface with safety profile seal (SPS).
Profile spacing:	< 8 mm in accordance with DIN EN 13451-1 and DIN EN 16582-1 (to prevent areas where fingers could become trapped)
Height (mm)	37
Connection	Fibre-glass reinforced polyester pipes as connection elements
Comment	Water drainage
Special shapes	Yes
Water drainage	Yes
Usage area	Public shower areas  Barrier-free shower areas  Footbaths
Dimensions	Produced to fit width and depth perfectly without the need for alignment profiles
Properties	Aesthetically pleasing Good water drainage Corrosion-free Excellent non-slip properties



## emco floor gratings

# **Model 772**

# Service and services Dimensioning Installation service Repairs