

# Model CARE



**Description**

High-quality look for effective, long-lasting protection of all high-grade floor coverings behind the clean-off zone.



Anti-static



Castor-resis-  
tant



Suitable for  
stairs



DS (EN 13893)



Resistant  
strength



Cfl-s1



High



Highly  
suitable for  
property

**Colours**



47.01 anthracite



47.02 grey



47.03 brown



47.04 beige



47.05 blue

# Model CARE

|                                       |   |
|---------------------------------------|---|
| <b>Construction</b>                   | Tufting velour 5/32"  |
| <b>Pile above substrate</b>           | 100% polyamide  |
| <b>Substrate material</b>             | Polyester fleece  |
| <b>Backing material</b>               | Heavy coating   |
| <b>Pile weight / fibre weight</b>     | 1005  |
| <b>Total weight (g/m<sup>2</sup>)</b> | 3650  |
| <b>Overall height (mm)</b>            | 7.5   |
| <b>Tuft density/m<sup>2</sup></b>     | 73100   |
| <b>Slip resistance</b>                | DS (EN 13893)   |
| <b>Certificates</b>                   | CE conformity EN 14041 (rolls only)   |
| <b>Supplied as rolls</b>              | 200 cm wide (incl. border)  |
| <b>Product characteristics</b>        | Soiling and moisture absorption   |
| <b>Laying</b>                         | Individual rolls or smaller coverings can be laid loose on any smooth floor. For larger areas, and allowing for on-site conditions, we recommend fixed laying with an adhesive suitable for plasticised PVC.  |
| <b>Cleaning</b>                       | Dirt removal with powerful brush vacuum cleaner. The spray extraction process is recommended for periodic basic cleaning. Cleaning with plenty of water is absolutely no problem, water temperature should not be above 40°C. Do not use chlorinated hydrocarbon (Tetra). |
| <b>Brand</b>                          | emco  |

Subject to technical modifications