

emco Bau

emco swimming pool grates 721/35

Special colours	The majority of special colours (according to RAL or tile sample) are available.
Profile run	Rigid swimming pool grating with grating bars running parallel to the pool edge
Description	Swimming pool grating that is robust, solid and pleasant to walk on, which efficiently collects the overflow water at the edge of the pool and provides maximum safety and hygiene.
Material	High quality, extremely hard-wearing plastic, with UV absorber. Entirely corrosion-free and resistant to chlorine, sea water and spa water. No need for any metal parts; surface enclosed on all sides to provide maximum hygiene.
Support chassis	Full profile (35 x 10 mm)
Finish	Flat upper profile surface with safety profile seal (SPS).
Profile spacing:	< 8 mm in accordance with DIN EN 13451-1 and DIN EN 16582-1 (to prevent areas where fingers could become trapped)
Height (mm)	35 mm
Connection	Fibre-glass reinforced polyester pipes as connection elements
Slip resistance	Non-slip in accordance with DIN 51097, classification C - tested by the "Institut der Säurefließner-Vereinigung" (Säurefließner consortium)
Variable grating width (mm)	100-340
Service and services	Dimensioning Installation service Repairs
Contact	emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems) · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de · www.emco-bau.com
Colours	Beige - similar to RAL 1001 Yellow - similar to RAL 1018 Grey - similar to RAL 7001 White - similar to RAL 9010