

emco Bau

emco swimming pool grates 760

Special colours	On demand
Profile run	Rigid swimming pool grating with grating bars running at right angles to the pool edge
Description	Swimming pool grating that is robust, solid and pleasant to walk on, which efficiently collects the overflow water at the edge of the pool and provides maximum safety and hygiene.
Material	No need for any metal parts; surface enclosed on all sides to provide maximum hygiene. Made from solid polypropylene (Hostalen®)
Support chassis	Full profile (22 x 10 mm)
Finish	Round upper profile surface with safety profile seal (SPS).
Profile spacing:	< 8 mm in accordance with DIN EN 13451-1 and DIN EN 16582-1 (to prevent areas where fingers could become trapped)
Height (mm)	22 mm
Connection	Every 3 elements permanently joined to form a standard length of 885 mm
Slip resistance	Non-slip in accordance with DIN 51097, classification C - tested by the "Institut der Säurefließner-Vereinigung" (Säurefließner consortium)
Grating width	200 mm 300 mm 400 mm
Variable grating width (mm)	110-399
Service and services	Dimensioning Installation service Repairs
Contact	emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems) · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de · www.emco-bau.com
Colours	Beige - similar to RAL 1001 Yellow - similar to RAL 1018 Grey - similar to RAL 7001 White - similar to RAL 9010