


emco DIPLOMAT With rubber insert

Model 522 TLS G



The emco entrance mat as a guidance system for the visually impaired



Description

The emco guidance system for the visually impaired is tactile and comes in high-contrast colours with different profile heights and profiles that run longitudinally to the direction of traffic, enabling blind and visually impaired people to find doors, stairs, lifts etc. as well as providing orientation in larger areas. Ideal guidance with cleaning effect through the entrance to the building. The guidance system also draws attention to obstacles and possible dangers. The floor guidance system can also facilitate orientation for people with no visual impairment. Optionally available with textured ground surface indicators and painted aluminium profiles.



Outside (Zone 1)



Street dust, hair, sand, ash, textile fibres, small leaves and twigs, loose chippings, coarse sand, small gravel particles



The emco entrance mat as a guidance system for the visually impaired

Colours



black

Model 522 TLS G

Approx. height (mm)	22
Roll-over and drive-over capability:	Wheelchairs Prams Light shopping trolleys hand trolleys
Standard profile clearance approx. (mm)	3 mm, rubber spacers
Connection	With threaded rod
Max. width/profile length for individual section (mm):	3000
available in the following widths (mm)	205, 264, 322, 381, 440, 499, 558 (alle Angaben in mm)
Depth/walking depth for individual section (mm):	3000
Weight (kg/m²)	14,4
Mat divisions as per factory standards or customer specifications	As of a profile length of 3000 mm or a maximum mat weight of 45 kg
Support chassis	made of rigid aluminium with sound insulation underlay. In the area of the tactile guidance system, the profiles are laid alternately in two heights. White and black aluminium profiles available.
Tread surface	Recessed, robust, weather-proof profiled rubber inserts.

Suitable for:

Hotel

emco DIPLOMAT With rubber insert

Model 522 TLS G

Service and services

Construction site advice

Measured using laser measuring device on site.

Fitting and installation service

Cleaning by mobile mat cleaning system

The product can be disposed of or recycled in an environmentally friendly way.

Accessories

emco installation frame 500: 500-25 AL Aluminium

emco installation frame 500: 500-25 CN Chrome-nickel steel (V2A)

emco installation frame 500: 500-25 MS Natural brass

Rubber underlay 1 mm: GU 1

Rubber underlay 3 mm: GU 3

Rubber underlay 5 mm: GU 5

Mat joining brackets: MV Supplied as standard with mats in several parts

Subject to technical modifications

emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems) ·
Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de
· www.emco-bau.com

